

MULTIFUNCTIONAL DIGITAL SYSTEMS

SAP R/3 Printing Device Type File Installation Guide

e-STUDIO5520c/6520c/6530c

■ Trademarks

SAP, R/3, mySAP, mySAP.com, xApps, xApp, SAP NetWeaver, and other SAP products and services mentioned herein as well as their respective logos are trademarks or registered trademarks of SAP AG in Germany and in several other countries all over the world. All other product and service names mentioned are the trademarks of their respective companies.

■ Warning

You may not, nor cause or permit any third party to, modify, adapt, merge, translate, reverse compile, reverse assemble, or reverse engineer the Software. You may not use the Software, except in accordance with this license. No title to the intellectual property in the Software is transferred to you and full ownership is retained by TTEC or its suppliers. Source code of the Software is not licensed to you. You will be held legally responsible for any copyright infringement, unauthorized transfer, reproduction or use of the Software or its documentation.

CONTENTS

Trademarks	1
Warning	1

Chapter 1

Introduction.....	6
SAP Printing Environment.....	6

Chapter 2

Device Files	8
--------------------	---

Chapter 3

Installation.....	10
-------------------	----

Chapter 4

Verification of Device Type File	16
--	----

Chapter 5

Creation of Output Device	20
---------------------------------	----

Chapter 6

Verification of Output Device	26
-------------------------------------	----

Chapter 7

Editing the Device Type File	30
------------------------------------	----

Chapter 8


TOSHIBA eS6530C Series Specific Features and Configuration.....	38
Background Adjustment Selection.....	38

1

Introduction

This document describes the step-wise procedure to install and configure the device type for Toshiba e-STUDIO6530C Series printers in SAP R/3. SAP administrator can implement the printer specific features by inserting the necessary PCL/PCL commands given in the Device configuration section. The version of the SAP environment used is 4.7.

■ SAP Printing Environment



1. SAP Client raises the print Request.
2. SAP Server will pass on the request to SAP spool system based on type of printer selected by the Client program.
3. SAP spool system will consult Device type file (.PRI File) corresponding to the output device. Based on configuration and control information present in Device type file, it will generate Printing data and Control Information.
4. Based on the "Access method" configured for the output device, SAP Printing Subsystem will operate in the respective way

2

Device Files


Device type	Supported features	Limitation
ZTSB65C.PRI	Color printing is supported for ABAP listing and SAP forms.	Cover page printing is not supported for ABAP listing.
ZTSB65CA.PRI	Color printing is supported for SAP forms.	Color Printing is not supported for ABAP list printing.

The installation procedure for "ZTSB65C.PRI" is described in this guide.
If you want to use the cover page printing function, install "ZTSB65CA.PRI".
However, color printing using ABAP cannot be performed.

3


Installation

To install a new device type into SAP, follow the procedure described below.
After you have logged on to SAP, the following screen is displayed.




© SAP is a trademark of SAP AG.

Click on the **“Spool Administration”** tab.




© SAP is a trademark of SAP AG.

Once you Press enter, the following screen is displayed.




© SAP is a trademark of SAP AG.

Press on the push-button **"Full administration"**. The following screen is displayed.




© SAP is a trademark of SAP AG.

In the menu bar, go to **"Utilities"** -> **"For device types"** -> **"Import"** as displayed in the following screen.




© SAP is a trademark of SAP AG.

Once you press “**Import**”, the following screen is displayed.




© SAP is a trademark of SAP AG.

Select the radio button “**Device Type**” and enter the name of the device type (.PRI) file without file extension in the input field box “**Object name**”. (E.g. if the device type file name is ZTSB65C.pri only ZTSB65C) as shown in the screen above. Make sure the entry in the field **Mode (EXPORT/IMPORT)** is written as “**IMPORT**”.




© SAP is a trademark of SAP AG.

Press “F8” to proceed with import. The following screen will be displayed.



© SAP is a trademark of SAP AG.


To locate the ZTSB65C.PRI (or ZTSB65CA.PRI) on local system, press Local Object . The following screen will be displayed.



© SAP is a trademark of SAP AG.

Locate the ZTSB65C.pri file (ZTSB65CA.pri file), and press **open**.
Import process will start as soon as **open** is pressed.

On successful completion of import, the following message would be displayed.




© SAP is a trademark of SAP AG.

4

Verification of Device Type File


Once the device type is imported, it needs to be verified whether the newly imported device type appears in the standard list of all device types in SAP R/3 or not. To verify this same, follow the steps given below.

In the initial screen of SAP, type the transaction code "**SPAD**" in the command window and press "Enter", the following screen is displayed.




© SAP is a trademark of SAP AG.

Click on **Full administration** and the following screen will be displayed.




© SAP is a trademark of SAP AG.

Click on the **Device Types**.



© SAP is a trademark of SAP AG.

On clicking on **Device Types**, list of device types will be displayed as in following screen.



© SAP is a trademark of SAP AG.


The newly imported device type **ZTSB65C** (or **ZTSB65CA**) should appear in this list of device type. If the **ZTSB65C** (or **ZTSB65CA**) is not displayed, it implies that import has not been successful for which the Installation procedure described earlier needs to be repeated and verified.

5

Creation of Output Device


In SAP R/3, a device type needs to be assigned to an Output device to utilise its printing features. Follow the procedure describe below to create an output device and assign a device type to it.

In the initial screen of SAP, type the transaction code "**SPAD**" in the command window and press "Enter", the following screen is displayed.




© SAP is a trademark of SAP AG.

Click on the "**Output devices**" and the following screen is displayed.



© SAP is a trademark of SAP AG.

Press on the **"Create"** button, the following screen will be displayed.




© SAP is a trademark of SAP AG.


- Enter the printer name (**BP** in the above mentioned example)
- Associate output device **ZTSB65C: eS6530C Series** device type.
- Make sure Device class is "Standard printer".

- Click **"Access Method"** to visit next part of output device configuration as shown in following screen.

Subsequently choose the appropriate **"Host Spool Access Method"** in the screen displayed below. Here it is selected as **"F"**.




© SAP is a trademark of SAP AG.



© SAP is a trademark of SAP AG.

Enter the **Host printer** name e-STUDIO6530C Series.

Click on **Output Attributes** to visit, next part of output device configuration.



5

© SAP is a trademark of SAP AG.


- (Optional), Administrator can enable printer for printing **cover page** by checking this check box.
- Press "**SAVE**" and the Output device will be created.

6

Verification of Output Device

Once the output device is created, it needs to be verified whether the newly created output device appears in the standard list of all output device in SAP R/3 or not. To verify this same, follow the steps given below.

In the initial screen of SAP, type the transaction code "**SPAD**" in the command window and press "Enter", the following screen is displayed.



© SAP is a trademark of SAP AG.

Click on the **Output devices** to get list of all output device configured on the SAP/R3 system. Newly created output device **BP** (or **BP CA**) should appear in this list.

Dev	Dev. Type	Spool servers	Location or message
BP	F ZTS865C		
CJVUP	F ZTS8205		Sarjapur-2
LP01	F XSF		Default Ent Printer
MASH	F ZTS845D		
PRINTER_65_1024	F WWIPS		
R10	F ZTS8850		
Test Printer	F UCPLAIN		
cj11	F ZTS8205		
cj2	F ZTS8205		
cj22	F ZTS8205		
cj2rc	F ZTS8205		
nags-cjrc	F ZTS8205		
zdevice	L SWIN	pdcent_ENT_00	
zloc	L SWIN	pdcent_ENT_00	
zpri	L SWIN	pdcent_ENT_00	

Output device BP was saved

ENT (1) (100) pdcent INS

© SAP is a trademark of SAP AG.


Newly created output device **BP** (or **BPCA**) should appear in the list. If newly created output device (NEW) is now displayed in the list, repeat the process of creating output device.

7


Editing the Device Type File

Once the device type is imported and verified whether the newly imported device type appears in the standard list of all device types in SAP R/3 or not, device type file can be edited as per the requirement. To edit the device type file, follow the steps given below.

In the initial screen of SAP, type the transaction code “**SPAD**” in the command window and press “Enter”, the following screen is displayed.




© SAP is a trademark of SAP AG.




© SAP is a trademark of SAP AG.

Click on the **Device Types**.




© SAP is a trademark of SAP AG.

On clicking on **Device Types**, list of device types will be displayed as in the following screen.




© SAP is a trademark of SAP AG.

- Select the device type file to be edited (**ZTSB65C** in the above mentioned example).
- Press “F8” to edit the selected device type file.
- Click “Formats” to view different types of formats of the selected device type file as shown in the following screen.




© SAP is a trademark of SAP AG.

Select the format to be edited by double clicking that format (**DINA4** in the above mentioned example). The following screen will be displayed.




© SAP is a trademark of SAP AG.

Select the section where the PJI is to be edited from the different sections available for the format (**Printer Initialization** section in the above mentioned example) by double clicking that section. The following screen will be displayed.



© SAP is a trademark of SAP AG.

Edit the data as per the user requirement as shown in the following screen.




© SAP is a trademark of SAP AG.

Suppose if the user wants to select the RENDERMODE value as GRAYSCALE instead of the default value AUTO, then


- Insert the comment(#) for the pjl RENDERMODE=AUTO.
- Remove the comment (#) for the pjl RENDERMODE=GRAYSCALE.

Press **"SAVE"**. The following screen will be displayed.



© SAP is a trademark of SAP AG.

Press **"SAVE"** again. The following screen will be displayed.



© SAP is a trademark of SAP AG.

The edited data will be saved in the selected format (DINA4).

■ Background Adjustment Selection

Following PjL would be used to achieve background adjustment selection:

Background Adjustment value is in the range between -4 and 4.

@PjL COMMENT DSSC PRINT BACKGROUND ADJUSTMENT=ZZ\r\n
(ZZ: -4=FC,-3=FD,-2=FE,-1=FF,0=00,1=01,2=02,3=03,4=04)

Suppose if the user wants to select the background adjustment value as 4, then the Background adjustment pjl would be

@PjL COMMENT DSSC PRINT BACKGROUND ADJUSTMENT=04\r\n

MULTIFUNCTIONAL DIGITAL SYSTEMS
SAP R/3 Printing Device Type File Installation Guide

e-STUDIO5520c/6520c/6530c

TOSHIBA TEC CORPORATION

2-17-2, HIGASHIGOTANDA, SHINAGAWA-KU, TOKYO, 141-8664, JAPAN

