



e-STUDIO™ 3525ACG/4525ACG/5525ACG

Introducing a new generation of multifunction printers (MFPs) – with high-performance, advanced security and cloud-ready features, these printers are the perfect choice for today's modern work environments.

- Highly Productive Color MFPs
- High-speed - 35, 45 & 55 PPM
- TAA Compliant
- Leading-edge Security Features
- CAC/PIV Authentication
- Cloud Print & Service Capabilities



Main Specifications

Copy System	Indirect Electrostatic Photographic/OPC/Laser Printing/Heat Roller Fusing 10.1" Color WSVGA Touch Screen Tilting Display 35/45/55 PPM (LT) Color: Less than 7.8/5.7/5.6 seconds Monochrome: Less than 5.9/4.4/4.3 second From Powering on: Approx 20/20/26 seconds From Sleep & Low Power: Less than 12/12/20 seconds 600 x 600 dpi 3.9" x 5.8" to 12" x 18", 12" x 47" Banner, Envelope Up to 999 Copies Standard 1,200 Sheets/Max. 5,200 Sheets 300-Sheet DSDF or DSDF with Double Feed Detection or 100-Sheet RADF LD/A3 Drawer 1: 550 Sheets-ST-R to LD Drawer 2: 550 Sheets-ST-R to 12" x 18" Stack Feed Bypass: 100 Sheets-3.9" x 5.8" to 12" x 18", 12" x 47" Banner Opt. 550-Sheet Paper Feed Pedestal-ST-R to 12" x 18" Opt. 550-Sheet Drawer for PFP-ST-R to 12" x 18" Opt. Envelope Cassette for PFP-Approx. 60 Envelopes/550 Sheets-ST-R to LG Opt. 2,000-Sheet Tandem LCF (Pedestal Type)-LT Only Opt. 2,000-Sheet External LCF-LT Only Standard: 550 Sheets x 2-16lb Bond-110lb Cover Stack Feed Bypass: 100 Sheets-14lb Bond-110lb Cover Opt. 550-Sheet Paper Feed Pedestal-16lb Bond-110lb Cover Opt. 550 Sheets Drawer for PFP-16lb Bond-110lb Cover Opt. Envelope Cassette for PFP-16lb Bond-140lb Index Opt. 2,000-Sheet Tandem LCF (Pedestal Type)-17lb-28lb Bond Opt. 2,000-Sheet External LCF-LT 16lb Bond-110lb Cover Standard Automatic Duplex Unit (16lb Bond-140lb Index) 25% to 400% Max 105K/105K/106K Month (Color: 100%) Max 210K/210K/212K Month (Monochrome: 100%) Approx. 169lb/172lb/173lb 23" (W) x 25.2" (D) x 31" (H) CMY: 38K, K: 39.8K @ 5% 120 Volts, 50/60 Hz, 12 Amps Maximum 1.8kW (120V) NEMA 5-15 8GB 128GB Solid State Drive (SSD), 512GB FIPS 140-2 SSD
Copy Resolution	
Stack Feed Bypass	
Multiple Copying	
Paper Capacity	
Original Feed	
Max. Original Size	
Paper Feed Sizes	
Paper Weights	
Duplex	
Reproduction Ratio	
Max Duty Cycle	
Weight	
Approx. Dimensions	
CMYK Toner Yield	
Power Source	
Power Consumption	
Plug Type	
Memory	
Hard Disk Drive	

e-BRIDGE Next Print Specifications

PDL	PCL5e, PCL5c, PCL6 (PCL XL), PS3, PDF, XPS, JPEG
Print Resolution	600 × 600 dpi (5 bit), 1,200 × 1,200 dpi (Color/2 bit) or 3,600 (Equivalence) x 1,200 dpi (BW/with Smoothing) (PS3 Only) Windows® 8.1/10, 11, Windows Server® 2012/R2, Windows Server® 2016/19/22, Macintosh® (macOS X 10.10-15, 12), Unix®, Linux® TCP/IP (IPv4, IPv6), NetBIOS over TCP/IP, IPX/SPX® for Novell® Environments, EtherTalk for Macintosh Environments SMB V1-3, LPR/LPD, IPP V1.2 w/Authentication (TLS 1.2/1.3), AppleTalk® PAP or EtherTalk, Port 9100 (Bi-Directional), NetWare P-SERVER LPD w/iPrint, Bluetooth (HCRP/BIP/OPP/FTP), WS Print, FTP Windows® 8.1 (32-bit, 64-bit), Windows Server® 2012/R2 (64-bit), Windows Server® 2016/19/22, Windows® 10, 11 (64-bit), macOS X 10.12-15, 11, 12 RJ-45 Ethernet (10/100/1000 Base-T), USB 2.0 (High-Speed) Optional IEEE802.11b/g/n, Wireless LAN, Optional Bluetooth AirPrint®, Mopria®, e-BRIDGE Print & Capture Application on iOS and Android (Available via Apple® App Store or Google Play) TopAccess Up to 10,000 Users or 1,000 Departments Supports User Authentication (on Device), Login Name/Password (via Windows® Domain) or Login Name/Password (via LDAP Server) for Copy, Print, Scan, Fax, List, and User Function
Operating Systems	
Network Protocols	
Printing Protocols	
Print Drivers	
Interface	
Wireless Device	
Device Management	
Account Control	
Accessibility Features	



Security Features

User Authentication, Trusted Platform Module, On-Board Data Scramble Function, SCEP, Disable, e-Filing, Disable Copy, Disk Overwrite* , IP Address Filtering (10 Sets), MAC Address Filtering (10 Sets), Network Service Control, Network Port Control, SMB Packet Signing, SSL/TLS (HTTP, IPP, LDAP, SMTP, POP, FTP, DPWS, SYSLOG), IPsec (IKEv1, IKEv2), Security Mode Change, CC Certified (ISO/IEC15408)* with HCD-PP v1.0, IEEE802.1X (Wired/Wireless), Digital Signature for Client Utilities, Password Policy, Password Lock, Password Expiration, Self Testing, Job Access Control, Log Access Control for Job Log, Security Stamp, Role Based Access Control, Secure PDF, Digital Signature for Firmware Update, Integrity Check Function, Image Log, Card Authentication, Biometric Authentication *Requires FIPS HDD, Conformance with HCD-PPv1.0 in High Security Mode
ENERGY STAR® (V3.1), EPEAT Gold, Californian Proposition 65
WHQL (Windows® 8, 8.1, 10, 11, 2012, 2012 R2, 2016/19/22),
Novell®, Citrix®, SAP, AirPrint® and Mopria®

Environmental Standards Certifications

Scan Specifications

Scan Speed	DSDF Scan: Up to 240 IPM Duplex, 120 IPM Simplex (Monochrome or Color) RADF Scan: Up to 73 IPM (Monochrome or Color) DSDF Simplex or Duplex: 9.3-110lb Bond RADF Scan: Simplex: 9.3-41.8lb Bond, Duplex: 13.3-41.8lb Bond Standard: Full Color, Auto Color, Monochrome, Grayscale DOC/XLS/PPT/PDF 600 dpi, 400 dpi, 300 dpi, 200 dpi, 150 dpi, 100 dpi Monochrome: TIFF-Multi/Single Page, PDF-Multi/Single Page, PDF/A, Searchable PDF, XPS-Multi/Single Page, DOCX, XLSX, PPTX Color/Grayscale: JPEG, TIFF-Multi/Single Page, PDF-Multi/Single Page, PDF/A, Slim PDF, Searchable PDF, XPS-Multi/Single Page, DOCX, XLSX, PPTX Color/Grayscale: JPEG (High, Middle, Low)
Scan Weights	
Scan Modes	
OCR	
Scan Resolution	
File Formats	
Image Compression	

Facsimile Specifications

Compatibility	Super G3
Data Compression	MH/MR/MMR/JBIG
Transmission Speed	Approx. 3 Seconds Per Page
Fax Modem Speed	Up to 33.6 Kbps
Memory Transmission	100 Jobs (with HDD), 2,000 Destinations Max. 400 Destinations/Job
Job	
Scan Speed	0.7 Seconds Per Page, Maximum 73 IPM

e-Filing Specifications

Operation Method	Color Touch Screen Control Panel or Client PC
Number of Boxes	1 Public Box, 200 Private User Boxes
Capacity of Boxes	100 Folders Per Box, 400 Documents Per Folder/Box, 200 Pages Per Document

Accessories (Options)

Platen & Document Feeder Options			
DSDF	MR4010	CAC/PIV Card Reader	SCR3310V2
DSDF with Double Feed Detection	MR4020	CAC/PIV Enabler	GS1013NODE
RADF	MR3033	IPSec Enabler	GP1080NODE
Platen Cover	KA5005PC	Unicode Font Enabler	GS1007NODE
Additional Paper Options		Multi-Station Print Enabler	
Paper Feed Pedestal	KD1072	Per Seat License	GS1090NODE
Drawer Module	MY1052	e-BRIDGE Plus for OneDrive	GB2300NODE
Envelope Cassette Option	MY1053	e-BRIDGE Plus for SharePoint	GB2310NODE
Large Capacity Feeder	KD1073LT	e-BRIDGE Plus for Exchange	GB2320NODE
External Large Capacity Feeder	MP2002	Workplace Productivity Bundle	GB2330NODE
Finishing Options*		e-BRIDGE Plus for Gmail	GB2380NODE
50-Sheet Inner Finisher	MJ1048	e-BRIDGE Plus for Google	
Hole Punch for MJ1048	MJ6011	Workspace	GB2390NODE
65-Sheet Staple Finisher	MJ1113	Hardcopy Security Printing	GP1190NODE
65-Sheet Saddle-Stitch Finisher	MJ1114	Security SSD (512GB)	GE1280
Hole Punch for MJ1113/MJ1114	MJ6107	FIPS HDD (320GB)	GE1260
Bridge Kit	KN5005	e-BRIDGE Plus Voice Guidance	GB2540NODE
Job Separator	MJ5015	e-BRIDGE Global Print	GB2550NODE
Connectivity/Security Options		Miscellaneous Options	
FAX Unit/2 nd Line for FAX Unit	GD1370N	Card Reader Holder	GR1320
Wireless LAN/Bluetooth	GN4030A3	Accessory Tray	GR1330
Fax Over IP License Key	GS1100NODE	Panel 10-Key Option	GR1340
Bluetooth Keyboard	GR9001	Stand	STAND5015
2 nd NIC Holder	GR1430	Work Tray	KK5005
USB Hub	GR1420	Manual Pocket	KK5008
Meta Scan Enabler	GS1010NODE	Harness for Coin Controller	GQ1280
		Accessible Arm	KK2560

*MJ1048 - 35 & 45 PPM models only

Designs and specifications subject to change without notice. Specifications may vary by conditions of use and/or environmental usage. For best results and reliable performance, always use supplies manufactured or designated by Toshiba. Not all options and accessories may be available at the time of product launch. Please contact a local Authorized Toshiba Dealership for availability. Toner yields are estimates based on 5% coverage, letter-size page. Driver and connectivity feature support varies by client/network operating system. AirPrint® and the AirPrint® logo are trademarks of Apple Inc. This is a Class 1 laser product complying with IEC60825-1. All company and/or product names are trademarks and/or registered trademarks of their respective manufacturers in their markets and/or countries.

Corporate Office

25530 Commercentre Drive, Lake Forest, CA 92630
Tel: 949-462-6000

East Coast

959 Route 46 East, 5th Floor, Parsippany, NJ 07054
Tel: 973-316-2700

Midwest

8770 W. Bryn Mawr Ave., Suite 700, Chicago, IL 60631
Tel: 773-380-6000

South

2037 Bakers Mill Rd., Dacula, GA 30019
Tel: 678-546-9385

West Coast

25530 Commercentre Drive, Lake Forest, CA 92630
Tel: 949-462-6000

Website

business.toshiba.com