

## **e-STUDIO™ 6527AC/7527AC**

Introducing a new generation of Toshiba departmental MFPs – with high-performance, zero-trust security and cloud-ready features, these printers are the perfect choice for today's modern work environments.

- Highly Productive Color MFPs
- High-speed – 65 & 75 PPM Color and 75 & 85 PPM Black & White
- Leading-edge Security Features
- Cloud Print & Service Capabilities
- Built-in Optical Character Recognition



## MAIN SPECIFICATIONS

<b>Copy System</b>	Indirect Electrostatic Photographic (OPC)/Laser Printing/Heat Roller Fusing
<b>Display</b>	10.1" Color WSVGA Touch Screen Tilting Display
<b>Copy Speed</b>	Color: 65/75 PPM (LT), Monochrome: 75/85 PPM (LT)
<b>First Copy Out</b>	Color: 6.4/5.4, Monochrome: 4.5/4.1 Seconds
<b>Warm-Up Time</b>	From Powering On: Approx. 20 Seconds
	From Sleep & Low Power: Less Than 15.4 Seconds
<b>Copy Resolution</b>	600 x 600 dpi
<b>Stack Feed Bypass</b>	3.9" x 5.8" to 12" x 18", 12" x 47" Banner, Envelope
<b>Multiple Copying</b>	Up to 999 Copies
<b>Paper Capacity</b>	Four Drawer Version: Standard 2,280 Sheets/Max. 6,780 Sheets
	Tandem Drawer Version: Standard 3,520 Sheets/Max. 8,020 Sheets
<b>Original Feed</b>	300-Sheet DSDF with Double Feed Detection
<b>Max. Original Size</b>	LD/A3
<b>Paper Feed Sizes</b>	Drawers: 540 Sheets-ST-R to 12" x 18"
	Integral Tandem LCF: 1,160 x 2 LT Only
	Stack Feed Bypass: 120 Sheets-3.9" x 5.8" to 13" x 19", 12" x 47" Banner
	Opt. 2,500-Sheet External LCF LT Only
	Opt. 2,000-Sheet Piggyback External LCF LT Only
<b>Paper Weights</b>	Drawers: Standard: 540 Sheets x 4-16lb Bond-110lb Cover
	Tandem LCF 1,160 Sheets x 2-16lb Bond-110lb Cover
	Plus 540 Sheets x 2-16lb Bond-110lb Cover
	Stack Feed Bypass: 120 Sheets-16lb Bond-110lb Cover
	Opt. 2,500-Sheet External LCF LT Only-16lb Bond-110lb Cover
	Opt. 2,000-Sheet Piggyback External LCF LT Only-16lb Bond-110lb Cover
	Standard Automatic Duplex Unit (16lb Bond-140lb Index)
<b>Duplex</b>	25% to 400%
<b>Reproduction Ratio</b>	540K/600K Month (Color: 100%)
<b>Max Duty Cycle</b>	Approx. 470lb
<b>Weight</b>	37.6" (W) x 27.5" (D) x 48.3" (H)
<b>Approx. Dimensions</b>	CMY: 39,200, K: 106,600 @ 5%
<b>CMYK Toner Yield</b>	120 Volts, 50/60 Hz, 16 Amps
<b>Power Source</b>	Maximum 2.0kW/2.4kW (120V)
<b>Power Consumption</b>	NEMA 5-20
<b>Plug Type</b>	6GB
<b>Memory</b>	128GB Solid State Drive (SSD)
<b>Hard Disk Drive</b>	

## e-BRIDGE NEXT PRINT SPECIFICATIONS

<b>PDL</b>	PCL5e, PCL5c, PCL6 (PCL XL), PS3, PDF, XPS, JPEG
<b>Print Resolution</b>	600 x 600 dpi, 1,200 x 1,200 dpi or 3,600 (Equivalence) x 1,200 dpi (BW/with Smoothing) (PS3 Only)
<b>Operating Systems</b>	Windows® 8.1, 10, 11, Windows Server® 2012/R2, Windows Server® 2016/19/22, Macintosh® (macOS X 10.10-15, 12), Unix®, Linux®
<b>Network Protocols</b>	TCP/IP (IPv4, IPv6), NetBIOS over TCP/IP, IPX/SPX® for Novell®
<b>Printing Protocols</b>	Environments, EtherTalk for Macintosh Environments
	SMB V1-3, LPR/LPD, IPP V1.2 w/Authentication (TLS 1.2/1.3), AppleTalk®
	PAP or EtherTalk, Port 9100 (Bi-Directional), NetWare P-SERVER LPD
<b>Print Drivers</b>	w/Print, Bluetooth (HCRP/BIP/OPP/FTP), WS Print, FTP
	Windows® 8.1 (32-bit, 64-bit), Windows Server® 2012/R2 (64-bit),
	Windows Server® 2016/19/22, Windows® 10, 11 (64-bit),
	macOS X 10.12-15, 11, 12
<b>Interface</b>	RJ-45 Ethernet (10/100/1000 Base-T), USB 2.0 (High-Speed)
<b>Wireless Device</b>	Optional IEEE802.11b/g/n, Wireless LAN, Optional Bluetooth
	AirPrint®, Mopria®, e-BRIDGE Print & Capture Application on iOS and
	Android (Available via Apple® App Store or Google Play)
<b>Device Management</b>	TopAccess
<b>Account Control</b>	Up to 10,000 Users or 1,000 Departments Supports User Authentication
	(on Device), Login Name/Password (via Windows® Domain) or Login
	Name/Password (via LDAP Server) for Copy, Print, Scan, Fax, List, and
	User Function
<b>Accessibility Features</b>	Tilt Front Panel, Job Programs, Universal Grip for Paper Trays, Disable
	Screen Timeout, Audible Beeps, Optional Voice Assist

## Security Features

User Authentication, Trusted Platform Module, On-Board Data Scramble Function, SCEP, Disable, e-Filing, Disable Copy, Disk Overwrite\*, IP Address Filtering (10 Sets), MAC Address Filtering (10 Sets), Network Service Control, Network Port Control, SMB Packet Signing, SSL/TLS (HTTP, IPP, LDAP, SMTP, POP, FTP, DPWS, SYSLOG), IPsec (IKEv1, IKEv2), Security Mode Change, CC Certified (ISO/IEC15408)\* with HCD-PP v1.0, IEEE802.1X (Wired/Wireless), Digital Signature for Client Utilities, Password Policy, Password Lock, Password Expiration, Self Testing, Job Access Control, Log Access Control for Job Log, Security Stamp, Role Based Access Control, Secure PDF, Digital Signature for Firmware Update, Integrity Check Function, Image Log, Card Authentication, Biometric Authentication

\*Conformance with HCD-PPV1.0 in High Security Mode

ENERGY STAR® (V3.1), EPEAT Gold, Californian Proposition 65

WHQL (Windows® 8, 8.1, 10, 11, 2012, 2012 R2, 2016/19/22), Novell®, Citrix®, SAP, AirPrint® and Mopria®

## Environmental Standards Certifications

## SCAN SPECIFICATIONS

<b>Scan Speed</b>	DSDF Scan: Up to 240 IPM Duplex, 120 IPM Simplex (Monochrome or Color)
<b>Scan Weights</b>	9.3-110lb Bond
	RADF Scan: Simplex: 9.3-41.8lb Bond, Duplex: 13.3-41.8lb Bond
<b>Scan Modes</b>	Standard: Full Color, Auto Color, Monochrome, Grayscale
<b>OCR</b>	DOC/XLS/PPT/PDF
<b>Scan Resolution</b>	600 dpi, 400 dpi, 300 dpi, 200 dpi, 150 dpi, 100 dpi
<b>File Formats</b>	Monochrome: TIFF-Multi/Single Page, PDF-Multi/Single Page, PDF/A, Searchable PDF, XPS-Multi/Single Page, DOCX, XLSX, PPTX
	Color/Grayscale: JPEG, TIFF-Multi/Single Page, PDF-Multi/Single Page, PDF/A, Slim PDF, Searchable PDF, XPS-Multi/Single Page, DOCX, XLSX, PPTX
<b>Image Compression</b>	Color/Grayscale: JPEG (High, Middle, Low)

## FACSIMILE SPECIFICATIONS

<b>Compatibility</b>	Super G3
<b>Data Compression</b>	MH/MR/MMR/JBIG
<b>Transmission Speed</b>	Approx. 3 Seconds Per Page
<b>Fax Modem Speed</b>	Up to 33.6 Kbps
<b>Memory Transmission</b>	100 Jobs (with HDD), 2,000 Destinations Max. 400 Destinations/Job
<b>Scan Speed</b>	0.7 Seconds Per Page, Maximum 73 IPM

## e-FILING SPECIFICATIONS

<b>Operation Method</b>	Color Touch Screen Control Panel or Client PC
<b>Number of Boxes</b>	1 Public Box, 200 Private User Boxes
<b>Capacity of Boxes</b>	100 Folders Per Box, 400 Documents Per Folder/Box, 200 Pages Per Document

## ACCESSORIES (OPTIONS)

Additional Paper Options	Software Options	
Large Capacity Feeder - 2,500 Sheet	e-BRIDGE Global Print	GB2550NODE
Large Capacity Feeder - 2,000 Sheet	IPSec Enabler	GP1080NODE
LCF Connector (to Add 2K LCF)	Unicode Font Enabler	GS1007NODE
<b>Finishing Options</b>	Multi-Station Print Enabler	
65-Sheet Staple Finisher	Per Seat License	GS1090NODE
65-Sheet Saddle-Stitch Finisher	e-BRIDGE Plus for OneDrive	
Hole Punch for MJ1115/MJ1116	for Business V3.0	GB2300NODE
Exit Tray	e-BRIDGE Plus for SharePoint	
<b>Connectivity/Security Options</b>	Online V3.0	GB2310NODE
FAX Unit/2 <sup>nd</sup> Line for FAX Unit	e-BRIDGE Plus for Exchange	
Wireless LAN/Bluetooth	Online V3.0	GB2320NODE
Fax Over IP License Key	Workplace Productivity Bundle	GB2330NODE
Bluetooth Keyboard	e-BRIDGE Plus for Gmail	GB2380NODE
2 <sup>nd</sup> NIC Holder	e-BRIDGE Plus for Google	
USB Hub	Workspace	GB2390NODE
Meta Scan Enabler	e-BRIDGE Plus Voice Guidance	GB2540NODE
Security SSD (512GB)		
FIPS HDD (320GB)		
<b>Miscellaneous Options</b>		
Card Reader Holder		
Accessory Tray		
Panel 10-Key Option		
Manual Pocket		
Harness for Coin Controller		
Accessible Arm		



Designs and specifications subject to change without notice. Specifications may vary by conditions of use and/or environmental usage. For best results and reliable performance, always use supplies manufactured or designated by Toshiba. Not all options and accessories may be available at the time of product launch. Please contact a local Authorized Toshiba Dealership for availability. Toner yields are estimates based on 5% coverage, letter-size page. Driver and connectivity feature support varies by client/network operating system. Product names may be trademarks of their respective companies. AirPrint® and the AirPrint® logo are trademarks of Apple Inc. This is a Class 1 laser product complying with IEC60825-1. All company and/or product names are trademarks and/or registered trademarks of their respective manufacturers in their markets and/or countries.

## Corporate Office

25530 Commercentre Drive, Lake Forest, CA 92630  
Tel: 949-462-6000

## East Coast

959 Route 46 East, 5th Floor, Parsippany, NJ 07054  
Tel: 973-316-2700

## Midwest

8770 W. Bryn Mawr Ave., Suite 700, Chicago, IL 60631  
Tel: 773-380-6000

## South

2037 Bakers Mill Rd., Dacula, GA 30019  
Tel: 678-546-9385

## West Coast

25530 Commercentre Drive, Lake Forest, CA 92630  
Tel: 949-462-6000

## Website

business.toshiba.com