TOSHIBA

E-STUDIO 9029AG

Introducing a new generation Toshiba multifunction printer (MFP) – with high-performance, zero-trust security and cloud-ready features, this printer is the perfect choice for today's modern work environments.

- High-Speed Up to 90 PPM
- TAA Compliant
- Advanced Security Features
- CAC/PIV Authentication
- Solutions Ready
- Environmentally Friendly





Main Specifications

Copy Process Indirect Electrostatic Photographic/OPC/Laser Printing/Heat Roller

Fusing

Display 10.1" Color WSVGA Touch Screen Tilting Display 90 PPM (LT)

Copy Speed First Copy Out

Monochrome: Less Than 5.2/4.5/4.1 Seconds From Powering On: Approx. 20/24/25 Seconds Warm-Up Time From Sleep: 15.4/15.4/Less Than 20 Seconds

From Low Power: 15.4 Seconds

600 × 600 dpi

Stack Feed Bypass 3.9" x 5.8" to 13" x 19", 12" x 47" Banner, Envelope

Multiple Copying Up to 999 Copies

Standard 3,520 Sheets/Max. 8,020 Sheets Paper Capacity Original Feed 300-Sheet DSDF with Double Feed Detection

Max. Original Size LD/A3

Copy Resolution

Drawers: 540 Sheets-ST-R to 12" x 18' Paper Feed Sizes

Integral Tandem LCF: 1,160 × 2 LT Only

Stack Feed Bypass: 120 Sheets-3.9" x 5.8" to 13" x 19", 12" x 47" Banner

Opt. 2.500-Sheet External LCF LT Only

Opt. 2,000-Sheet Piggyback External LCF LT Only **Paper Weights** Drawers: Standard 540 Sheets x 2-16lb Bond-110lb Cover Tandem LCF 1,160 Sheets x 2-16lb Bond-110lb Cover Stack Feed Bypass: 120 Sheets-16lb Bond-110lb Cover

Opt. 2,500-Sheet External LCF LT Only-16lb Bond-110lb Cover Opt. 2,000-Sheet Piggyback External LCF LT Only-16lb Bond-110lb

Cover Standard Automatic Duplex Unit (16lb Bond-140lb Index) Duplex

Reproduction Ratio Max Duty Cycle 740K Month Approx.430lb Weight

Approx. Dimensions 37.6" (W) x 27.5" (D) x 48.3" (H) Toner Yield 106.6K @ 5% 120 Volts, 50/60 Hz, 16 Amps **Power Source** Power Consumption Maximum 2.0kW/2.0kW/2.4kW (120V)

Plug Type NEMA 5-20

Hard Disk Drive 128GB Solid State Drive (SSD), 512GB FIPS 140-2 SSD

e-BRIDGE Next Print Specifications

PCL5e, PCL5c, PCL6 (PCL XL), PS3, PDF, XPS, JPEG

Print Resolution 600 × 600 dpi, 1,200 × 1,200 dpi or

3,600 (Equivalence) x 1,200 dpi (with Smoothing) (PS3 Only) Windows* 8.1,10, 11, Windows Server* 2012/R2, Windows Server* **Operating Systems** 2016/19/22, Macintosh® (macOS X 10.10-15, 12), Unix®, Linux® TCP/IP (IPv4, IPv6), NetBIOS over TCP/IP, IPX/SPX® for NovelI® **Network Protocols**

Environments, EtherTalk for Macintosh Environments **Printing Protocols** SMB V1-3, LPR/LPD, IPP V1.2 w/Authentication (TLS 1.2/1.3), AppleTalk® PAP or EtherTalk, Port 9100 (Bi-Directional), NetWare

P-SERVER LPD

w/iPrint, Bluetooth (HCRP/BIP/OPP/FTP), WS Print, FTP Windows® 8.1 (32-bit, 64-bit), Windows Server® 2012/R2 (64-bit), **Print Drivers**

Windows Server® 2016/19/22, Windows® 10, 11 (64-bit), macOS X 10.12-15, 11, 12

Interface RJ-45 Ethernet (10/100/1000 Base-T), USB 2.0 (High-Speed)

Optional IEEE802.11b/g/n, Wireless LAN, Optional Bluetooth Wireless Device

AirPrint[®], Mopria[®], e-BRIDGE Print & Capture Application on iOS and Android (Available via Apple[®] App Store or Google Play)

Device Management

Account Control Up to 10,000 Users or 1,000 Departments Supports User Authentication (on Device), Login Name/Password (via Windows®

Domain) or Login Name/Password (via LDAP Server) for Copy, Print, Scan, Fax, List, and User Function

Accessibility Features Tilt Front Panel, Job Programs, Universal Grip for Paper Trays, Disable Screen Timeout, Audible Beeps, Optional Voice Assist

Security Features

User Authentication, Trusted Platform Module, On-Board Data Scramble Function, SCEP, Disable, e-Filing, Disable Copy, Disk Overwrite*, IP Address Filtering (10 Sets), MAC Address Filtering (10 Sets), Network Service Control, Network Port Control, SMB Packet Signing, SSL/TLS (HTTP, IPP, LDAP, SMTP, POP, FTP, DPWS, SYSLOG), IPsec (IKEv1, IKEv2), Security Mode Change, CC Certified (ISO/IEC15408)* with HCD-PP v1.0, IEEE802.1X (Wired/ Wireless), Digital Signature for Client Utilities, Password Policy, Password Lock, Password Expiration, Self Testing, Job Access Control, Log Access Control for Job Log, Security Stamp, Role Based Access Control, Secure PDF, Digital Signature for Firmware

Update, Integrity Check Function, Image Log, Card Authentication, Biometric Authentication *Conformance with HCD-

PPv1.0 in High Security Mode

Environmental Standards

Certifications

ENERGY STAR® (V3.1), EPEAT Gold, Californian Proposition 65 WHQL (Windows' 8, 8.1, 10, 11, 2012, 2012 R2, 2016/19/22), Novell', Citrix', SAP, AirPrint' and Mopria'

Scan Specifications

Scan Speed DSDF Scan: Up to 240 IPM Duplex, 120 IPM Simplex

(Monochrome or Color)

Scan Weights 9.3-110lb Bond

Scan Modes Standard: Full Color, Auto Color, Monochrome, Grayscale OCR

DOC/XLS/PPT/PDF Scan Resolution

600 dpi, 400 dpi, 300 dpi, 200 dpi, 150 dpi, 100 dpi File Formats

Monochrome: TIFF-Multi/Single Page, PDF-Multi/Single Page, PDF/A, Searchable PDF, XPS-Multi/Single Page, DOCX, XLSX,

Color/Grayscale: JPEG, TIFF-Multi/Single Page, PDF-Multi/Single Page, PDF/A, Slim PDF, Searchable PDF, XPS-Multi/Single Page,

DOCX, XLSX, PPTX

Color/Grayscale: JPEG (High, Middle, Low) **Image Compression**

Facsimile Specifications

Compatibility Super G3

MH/MR/MMR/JBIG Data Compression Transmission Speed Approx. 3 Seconds Per Page

Fax Modem Speed Up to 33.6 Kbps

Memory Transmission

. 100 Jobs (with HDD), 2,000 Destinations Max.

400 Destinations/Job

e-Filing Specifications

Operation Method Color Touch Screen Control Panel or Client PC **Number of Boxes** 1 Public Box, 200 Private User Boxes

100 Folders Per Box, 400 Documents Per Folder/Box,

200 Pages Per Document

Accessories (Options)

Additional Paper Options

Capacity of Boxes

Large Capacity Feeder - 2,500 Sheet MP25031 Large Capacity Feeder - 2,000 Sheet MP2002L

LCF Connector (to Add 2K LCF) KN9000 **Finishing Options** 65-Sheet Staple Finisher MJ1115

65-Sheet Saddle-Stitch Finisher MJ1116 Hole Punch for MJ1115/MJ1116 MJ6108N Finisher Guide Rail KN1103 Exit Tray KA6551 Connectivity/Security Options

GD1370N FAX Unit/2nd Line for FAX Unit Wireless LAN/Bluetooth GN4030A3 Fax Over IP License Key GS1100NODE Bluetooth Keyboard 2nd NIC Holder GR9001 GR1430

Meta Scan Enabler CAC/PIV Card Reader CAC/PIV Enabler

USB Hub

South

Website

Miscellaneous Options Card Reader Holde

GR1320 Accessory Tray Panel 10-Key Option GR1330 GR1340 Manual Pocket KK5008 Harness for Coin Controller GQ1280 Accessible Arm KK2560

Software Options e-BRIDGE Global Print

GB2550NODE IPSec Enabler GP1080NODE Unicode Font Enabler GS1007NODE Multi-Station Print Enabler GS1090NODE

Per Seat License e-BRIDGE Plus for OneDrive for Business V3.0 GB2300NODE

e-BRIDGE Plus for SharePoint GB2310NODE

Online V3.0 e-BRIDGE Plus for Exchange Online V3.0 GB2320NODE

Workplace Productivity BundleGB2330NODE e-BRIDGE Plus for Gmail e-BRIDGE Plus for Google

Workspace e-BRIDGE Plus GB2380NODE GB2390NODE

Voice Guidance GB2540NODE













Designs and specifications subject to change without notice. Specifications may vary by conditions of use and/or environmental usage. For best results and reliable performance, always use supplies manufactured or designated by Toshiba. Not all options and accessories may be available at the time of product launch. Please contact a local Authorized Toshiba Dealership for availability. Toner yields are estimates based on 5% coverage, letter-size page. Driver and connectivity feature support varies by client/network operating system. Product names may be trademarks of their respective companies. AirPrint® and the AirPrint® logo are trademarks of Apple Inc. This is a Class 1 laser product complying with IEC60825-1. All company and/or product names are trademarks and/or registered trademarks of their respective manufacturers in their markets and/or countries.

25530 Commercentre Drive, Lake Forest, CA 92630 **Corporate Office** Tel: 949-462-6000 **East Coast** 959 Route 46 East, 5th Floor, Parsippany, NJ 07054

GR1420

GS1010NODE

GR1013NODE

SCR3310V2

Tel: 973-316-2700 8770 W. Bryn Mawr Ave., Suite 700, Chicago, IL 60631 Midwest Tel: 773-380-6000

2037 Bakers Mill Rd., Dacula, GA 30019 Tel: 678-546-9385

West Coast 25530 Commercentre Drive, Lake Forest, CA 92630 Tel: 949-462-6000 business.toshiba.com

@ 2025 Toshiba America Business Solutions, Inc. Electronic Imaging Division Inv. Code 22459 $\\ensuremath{\text{e-STUDIO9029AG}}$ Spec Sheet 1/25